




SK1-FSA-34/16/8-NBS-PP-M2/Y1

Ordercode: CS008P



Connector view Wiring Diagram



1) Potentiometer 2) LED function indicator



Electrical connection

Cable length	0.2 m
Connection	M8x1-Connector, 3-pole
Connection type	Cable with connector, 0.20 m, PUR
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

MTTF (40 °C)	462 a
Operating voltage U_b	12...30 VDC
Protected against miswiring	yes
Rated insulation voltage U_i	75 V DC
Rated operating current I_e DC	50 mA
Ready delay t_v max.	100 ms
Repeat accuracy max. (% of S_r)	5.0 %
Switching frequency	2 Hz
Utilization category	DC-13
Voltage drop static max.	1.5 V

Environmental conditions

Ambient temperature	-30...70 °C
Protection type IEC 60529	IP67

Functional safety

Diagnostic coverage	0 %
Functional safety	no

General data

Approval/Conformity	cULus;CE
Basic standard	IEC 60947-5-2
Scope of delivery	Holder
Sensitivity	media-dependent, adjustable
Series	Level sensor

Material

Cover material	PP
Housing material	PP
Material cover	PP
Material jacket	PUR
Material sensing surface	PP

Mechanical data

Dimension	34 x 16 x 8 mm
Installation	flush with container outer wall

Output/Interface

Switching output	NPN Normally open (NO)
------------------	------------------------

Range/Distance

Ripple max. (% of U_e)	10 %
---------------------------	------

Remarks

Note for using in standard applications with aqueous media: The Smart Level sensors are factory adjusted for standard applications. With this setting the Smart Level sensors can be used without further adjustment for detecting